



| 电气性能/Electrical | |
|--------------------------|-----------------------|
| 额定电压/Rated voltage | 300V |
| 额定电流/Rated current | 20A |
| 使用线径/Wire range | 22-12AWG |
| 耐电压/Withstanding voltage | AC1600V/1Min |
| 机械性能/Mechanical | |
| 温度范围/Temp. range | -40℃~+105℃ |
| 扭力/Torque | 4.43Lb-in |
| 尺寸/Dimenslons | |
| 间距/Pitch | 7.62mm |
| 极数/Poles | 2P-24P |
| 材质及电镀/Material | |
| 塑件/Housing | PA66, UL94V-0 |
| 螺丝/Screw | M3, steel Zinc plated |
| 焊针/Welding needle | Brass, Tin plated |

订购方式: HOW TO ORDER

□ - □ P - □ □ - □ □ □ □

客户需求
Custmor Request

| | | | | | | |
|---------------------|----------|----|-----------|----|----------------|----|
| 0.未定义/No definition | 灰色/Grey | 10 | 绿色/Green | 40 | 透明/Transparent | 70 |
| 1.单间距/Sing pitch | 蓝色/Blue | 20 | 橙色/Orange | 50 | 黄色/Yellow | 80 |
| 2.双倍间距/Double pitch | 黑色/Black | 30 | 红色/Red | 60 | 白色/White | 90 |

型号/Model 极数/POLE

NAME: LF421S/SP-7.62 (LF762)