



Dept Qty
DC 1
ED 1
IE 1
ISO 1
PD 1
R&D 1
SD 1
QA 1
QC 1
QE 1




The information provided herein is from CONNLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNLY or its affiliates. Unauthorized use or reproduction of this information in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, is strictly prohibited. CONNLY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.




W/ central




W/O central




Recommended PCB layout(Tolerance:±0.05)



(Series Image-Reference Only)



W/O Kink Figure



W/ Kink Figure

Position	Dimension			
	A	B	C	D
06	7.62	5.08	10.16	7.62
08	10.16	7.62	10.16	7.62
14	17.78	15.24	10.16	7.62
16	20.32	17.78	10.16	7.62
18	22.86	20.32	10.16	7.62
20	25.40	22.86	10.16	7.62
24	30.48	27.94	10.16	7.62
24	30.48	27.94	17.78	15.24
28	35.56	33.02	10.16	7.62
28	35.56	33.02	17.78	15.24
32	40.64	38.10	17.78	15.24
40	50.80	48.26	17.78	15.24
42	53.34	51.00	17.78	15.24

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1009-XXXXX-XXX-D		

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LJH 09/28/05'	~	LJC 09/28/05'
B	ADD W/ Kink Figure	LL 11/04/06'	~	LJC 11/04/06'
C	ADD P/N Code	LJC 12/10/13'	~	LJC 12/10/13'
D	DRAWING UPDATE	JLZ 08/14/18'	~	

NOTES:

1. Electrical characteristics:


- 1.1 Contact resistance: 20mΩ Max.
- 1.2 Dielectric withstanding voltage: 500V AC(rms) for 1 minute.
- 1.3 Insulation resistance: 1000MΩ Min.

2. Environment characteristics:

- 2.1 Temperature: -20°C~+105°C.

3. Product number code:

DS1009 -



Packing Type(Box):
2: 2 inner box/outer box
4: 4 inner box/outer box
6: 6 inner box/outer box

Product Packing Type:
A: Tube + Plastic Nail
B: Tube + Rubber
C: Foam Board

Housing Material:
0: PBT UL94 V-0
2: PBT UL94 HB

Central support
S: W/ central support
X: W/O centralsupport

Width(DIM D)
N: 7.62mm(06~28p)
W: 15.24mm(24~42p)

Contact plating
T1: Tin

Contact type
A: W/O kink
B: W/ kink

No.of contacts
06 08 14 16 18 20 24 28 32
40 42